



SONALI SOLAR

"Energy Inspired by Nature"

LEADING MANUFACTURER OF PV MODULES

3 to 30 Series



Quality Product

All Manufactured modules are tested 100% by EL (Electroluminescence) during the Production Process & Free from micro cracks.

Our high-performance modules are highly efficient, reliable and provide optimal output. The company manufactures solar modules in compliance with global standard including MNRE, IEC 61215, 61730-1, 61730-2, 61701, ISO 9001:2008 & ISO 14001:2008 & 18001:2007.

High Efficiency

High Module efficiency is obtaining top performance even in diffused light conditions. We are leaders in providing our customers with maximum sunlight conversion.

Application Possibilities

Residential and Commercial rooftops, Car ports, Solar Farming, Balconies, Awnings, Street lights, Fences, and Canopies.

Our Team

We have a team of qualified experts and engineers making sure that modules produce maximum power. We pride ourselves in caring for each individual customer needs with detailed attention. Our end goal is to give a highly efficient product with exceptional customer service.

RFID

RFID is an Radio Frequency Identification Technology - enables every individual modules to be uniquely identified. We can provide RFID tag as per customer's request.



An ISO 9001 : 2008 Certified
An ISO 18001 : 2007 Certified
An ISO 14001 : 2004 Certified

US OFFICE:

Sonali Energiees USA LLC.,
409 Grand Avenue, Suite 3,
Englewood, NJ 07631
Tel: 201-568-1424
Toll Free: 1.888.58.SOLAR
salesusa@sonalisolar.com
info@sonalisolar.com

Europe Office:

Sonali Solar Europe Limited
Moore Stephens (South)
City Gates, 2-4 South Gate,
Chichester, W. Sussex,
PO 19 8DJ
saleseurope@sonalisolar.com

Manufacturing Facility:

Plot No. 180-199
Surat Special Economic Zone
Sachin-Dist. Surat 394230
Gujarat, India
Tel: +91 0261 2399910
Ph.: +91 9978968011
sales@sonalisolar.com

Electrical Specifications

| Nominal Maximum Power (Pmax) | 3W | 5W | 8W | 10W | 12W | 15W | 18W | 20W | 25W | 30W |
|---------------------------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| Optimum Operating Voltage (Vmp) | 8.82 | 8.82 | 17.64 | 17.64 | 17.64 | 17.64 | 17.64 | 17.64 | 17.64 | 17.64 |
| Optimum Operating Current (Imp) | 0.34 | 0.57 | 0.46 | 0.57 | 0.68 | 0.85 | 1.02 | 1.13 | 1.42 | 1.70 |
| Open Circuit Voltage (Voc) | 10.8 | 10.8 | 21.6 | 21.6 | 21.6 | 21.6 | 21.6 | 21.6 | 21.6 | 21.6 |
| Short Circuit Current (Isc) | 0.37 | 0.61 | 0.48 | 0.61 | 0.73 | 0.92 | 1.09 | 1.20 | 1.53 | 1.82 |

Mechanical Specification

| Module Dimensions (LXWXT) | 200X200X18 mm | 315X200X18 mm | 240X355X18 mm | 300X355X18 mm | 340X355X18 mm | 395X355X18 mm | 470X355X18 mm | 505X355X18 mm | 640X355X18 mm | 745X355X18 mm |
|------------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Weight | 0.59kg/1.29lbs | 0.86kg/1.90lbs | 1.12kg/2.47lbs | 1.36kg/3.00lbs | 1.52kg/3.36lbs | 1.74kg/3.85lbs | 2.05kg/4.51lbs | 2.19kg/4.82lbs | 2.63kg/5.80lbs | 3.16kg/6.96lbs |
| Cell Arrangement | 18 (9X2) | 18 (9X2) | 36 (9X4) | 36 (9X4) | 36 (9X4) | 36 (9X4) | 36 (9X4) | 36 (9X4) | 36 (18X2) | 36 (18X2) |
| Front Cover (Tempered Glass) | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm | 3.2mm |
| Encapsulate | EVA | EVA | EVA | EVA | EVA | EVA | EVA | EVA | EVA | EVA |
| Back Cover | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet | Composite sheet |
| Junction Box | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal | 2 terminal |
| Mounting Holes Pitch (Y)-mm | 100 | 157.5 | 120 | 150 | 170 | 197.5 | 235 | 252.5 | 320 | 372.5 |
| Mounting Holes Pitch (X)-mm | 176 | 176 | 331 | 331 | 331 | 331 | 331 | 331 | 331 | 331 |

* Maximum System Voltage : 1000 V * Measurement Power Tolerance on Power $\pm 3\%$, 0 / + Tolerance on Max power Available upon request.

* Under Standard Test Conditions (STC) of irradiance of 1000W/m², spectrum AM 1.5 and cell temperature of 25 °C

Other Characteristics

Junction Box : Weather proof Nylon
 Type of Cell : Mono / Multi Crystalline Silicone
 Temp. Coefficients : Coefficient of Current (α) - (0.060 %/°C)
 Coefficient of Voltage (β) - (-0.35 %/°C)
 Coefficient of Power (λ) - (-0.45%/°C)

* Certification : Complied to IEC 61215, 61730-1, 61730-2 & 61701, MNRE Approved.

* The Standard range of modules is supplied without diodes. However, diodes can be provided on specific customer request at extra cost.

* Due to constant product modifications, SONALI SOLAR reserves the right to amend.

www.sonalisolar.com



Tested Operating Conditions:

Temperature Cycling Range : (-40°C~+85°C)
 humidity Freeze, Damp Heat : 85 % RH

Mounting Details

All dimensions in mm and tolerances ± 2 mm

